

DEEP ROOF LIGHTING INC.

P.O. BOX 520191, FLUSHING, NY 11352

Tel: 718-243-9388, 718-243-1185, 718-243-1188, 718-637-6061

Fax: 718-243-9403, 718-321-1676

Web Site: www.deeprooflighting.com

Email: deeproof@aol.com deeproof@verizon.net deeproofgg@gmail.com

LED cabinet spot lights - UL listed



Input 100 - 130 VAC
Power - 7 Watts
Angel - 45°
Lumen Range - 450 - 500
Not for dimming
Warranty - 3 years
UL, ULc listed
Over power protection
Short circuit protection



Puck Socket:



PMMA cover for lens, 94% high light transmittance, make sure that the light spread is softly and balanced.. Electric circuit with PFC construction could effectively increase power factor more than 0.92,

and greatly decrease the harmonic current impulse, helpful for power saving.

Heating sink is designed base on "Module thermal balanced" and "Module thermal separation"

so that the heat in led and led driver be separated to assure driver and led longer life.

Aluminum alloy lamp housing with streamline outlook, made by high thermal conductivity and precision lathe,

could fully export the led quantity heat and reduce the light dissipation effectively.

CRI , light efficiency ,light degradation all in coincident with LM79 and LM80(energy saving star Dust-proof up to IP6X

Gray socket

White socket





<u>Item Codes:</u>

LSP7W-WA: white socket, Metal puck light, warm white 2700-3300 K
LSP7W-CA: white socket, Metal puck light, cool white 4000-4500 K
LSP7W-DA: white socket, Metal puck light, daylight 6000-6500 K
LSP7S-WA: Gray socket, Metal puck light, warm white 2700-3300 K
LSP7S-CA: Gray socket, Metal puck light, cool white 4000-4500 K
LSP7S-DA: Gray socket, Metal puck light, daylight 6000-6500 K





